





Product Code	OSA-ACY-70033iV6		
Description	Rainjoy Lumos shower 480X330mm RGB LED front panel with AISI 304 stainless steel base plate included remote control & installation kit for false ceiling - Chromo therapy (RGB): LED 28.8W with 12V 3A Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz - 2-functions - Rain - 4 X Mist (Compatible with iV6)		
Flow Rate	Rain - 42.30 LPM @ 3 bar Mist - 8.00 LPM @ 3 bar		
Recommended Water Pressure	2.0 - 4.0 Bar Min.		
Min & Max Water Temperature	5°C ~ 75°C		
Mount Type	Ceiling Mounting		
Spray Modes	Rain & Mist Functions		
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) Acrylic: Acrylic 6T = 6mm thick Acrylic sheet.		
REMOTE CONTROL	RGB Remote Control Remote Option: RGB Working Voltage: 3Vd c Wireless Frequency: 2.4GHz Working Temperature: -5C-55C	Indicator Light ON/OFF Mode Key Mode Key Mode Key Mode Key Service R G Red/Green/ B Blue LED Keys R G Red/Green/ B Saturation Short press: ON/OFF Long press: Adjust Scene Keys I II Short press to play Long press to save	
IP Rating	1- LED Panel (IP4) 2- SMPS Box (IP7) which includes RGB controller inside		
LED Specification	RGB LED Voltage: 12Vdc (minimum electricity goes through LED panel for the user safety) RGB LED Watt: 28.8W		

POWER SUPPLY	Power Supply (SMPS) Including Controller INPUT : AC 100-240V, 50-60Hz OUTPUT : 12V - 3A	
RGB Color Variations	COLOR VARIATION • Mono Color (RGB)	Chromo Theraphy LED On / Off Switch Sensor by Remote Control

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.